

DN-32516C

8MP 16CH NVR



Specification:

Model		DN-32516C
System	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
Video	Format	IP-CAM with ONVIF Profile S/T support
	Input	IP-CAM: Up to 16-CH, 8MP/CH
	Output	HDMI: up to 3840x2160 , VGA: up to 1920x1080 ; CVBS
Record	Compression	Audio: ADPCM
	Recording Resolution:	8MP/5MP/4MP/3MP/1080p/720p/720x480 (Full Channel Support)
	Mode	Manual/Schedule/Alarm/Motion
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Audio	Input	1 RCA-jack connectors, line-in level (0.1-1Vrms)
	Output	HDMI ; 1 RCA-jack connectors, line-out level < 1Vrms
Display	Split windows	1/4/7/9/16
	Frame rate	Up to 30/25fps per display window
	Digital Zoom	X2, X4, X8, X16
Playback	Max frame rate	120fps@8MP / 200fps@5MP / 480fps@1080p / 960fps@720p (Full Channel Support)
	Synchronous Playback:	16 ch (480fps@2MP)
	Search	Date/time, Camera, Alarm, Motion & Video Loss
	Operation	Play, Fast Forward, Backward, Pause, Stop, Snapshot, etc.
Storage	HDD	1 x 3.5" SATA HDD
	Backup	1 USB 3.0 port & 1 USB 2.0 port
Alarm	Input	4 contact (Low Active); support alarm inputs of IP-CAM
	Output	1 Normally Open or Normally Closed relay output
Network Interface & Others:	Incoming bandwidth:	Up to 300Mbps incoming bandwidth including live display
	Ethernet	1 x RJ-45 10M/100M/1G Ethernet connector
	Push alarm / Cloud	App Push alarm ; Alarm recording to Google Cloud Drive
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP, NTP, RTSP, UPnP, P2P
	Remote users	Up to 8 users simultaneously
Control	Remote	Support Windows 11/10/8/7, N-streaming live view, IE/Edge/Chrome for DVR, App for Mac/iPhone/iPad/Android phone and Tablet PC
	RS-485	2-pin for keyboard, POS and/or PTZ control
Setup	Local	On screen setup remote controller, USB mouse, and/or RS-485 keyboard controller
	Remote	Setup & upload via Windows/Mac/iPad/Android phone application software
Reliability	System recovery	Auto power on after power loss recovery; Watch Dog Timer
	Security	Multi-level password (4 levels, up to 18 accounts) protection for remote access
Weights & Measures		318(W) x 209(D) x 49.2(H)mm, 4.5KG (without HDD)
Power	Source / Consumption	+12VDC, 3A / 36W Max.
Operating Temperature		-20C ~ 65C